Helix Operations Management Adapter

Adapters · https://2yetis.net/docs/helix-operations-management-adapter/

The Helix operations Management adapter allows you to send events to helix operations management.

Configuration:

Parameter	Type	Default	Description
url	string	n/a	The URL used to access the Helix Operations Management system
key	string	n/a	The key used to identify agains the Helix Operations Management system
secret	string	n/a	The secret used to identify against the Helix Operations Management system
tenantId	string	n/a	The Tenant ID to connect to
jwtRefreshInterval	Number	300	The interval in seconds used by the adapter to refresh the jwt token received by Helix. The jwt token is used to access the Helix server after login. It expires after a certain interval. The adapter will refresh the token automatically after the specified time.

Example:

```
- driver: "net.the2yetis.uvuyo.integration.helix.HelixEventAdapter"
  active: true
  id: "helixEventAdapter"
  name: "BHOM"
  dispatcherId: "snmp2helix"
  ruleModules: ["log"]
  url: https://customerdev.onbmc.com
  key: I5FC96MJWDD2WQXESD6sVH2EC8O68BKD
  secret: MtTsZrqyyTlnm7FzUrt7NdsPuBJW2xT2YdLWuoDTSmN2zkKPp
  tenantId: 9999999
  jwtRefreshInterval: 300
```